



上海查尔斯电子有限公司


3-3

Date: 2008/12/31

## \*Tape And Reel Of GH-S106 Series


SEC.A-A

-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050
-0.050



Rev: C

Stand All din	nsions per ANSI/EIA ard RS-481 nensions are in eters (inches).
Α	180[7.09]
В	60[2.36]
С	13.5[0.53]
W	8.4[0.33]
	ess of top cover tape 104"] MAX



## NOTES:

- 1. Empty component pockets are sealed with top cover tape;
- 2. Minimum leader length at both ends of the tape is 450 mm;
- 3. The maximum number of missing lamps is two;
- 4. The cathode is oriented towards the tape sprocket hole;
- 5. 2,000pcs/Reel