

① REFLECTOR COATING TYPE HIGH-PERFORMANCE LEDs


反射蓋灌注型高效率發光二極體

GH-2510 Series Electro-Optical Characteristics:

Code for parts GH-XXXXX	Lighting Color	Material	V _F (V)		λ (nm)			I _V (mcd)	Internal Circuit
			Typ	Max	λ _D	λ _P	Δλ	Min	
RQDA10TZ-WPE	Red	AlGaInP	2.00	2.50	630	640	20	85	
OVDA10TZ-WPE	Orange	AlGaInP	2.20	2.70	624	635	20	95	
YUDA10TZ-WPE	Yellow	AlGaInP	2.00	2.50	590	595	20	95	
GBDA10TZ-WPJ	Green	AlGaInP	2.00	2.50	574	575	20	30	
G3JA10TZ-WPH	Green	GaInN	3.30	3.80	525	520	30	190	
BLJA10TZ-WPH	Blue	GaInN	3.50	4.00	465	460	30	45	
WVJA10TZ-WPH	White	GaInN	3.50	4.00	X=0.22~0.38 Y=0.22~0.36			290	



② Package Outline Drawing:




- NOTES: 1. All dimensions are in millimeters (inches);
2. Tolerances are $\pm 0.2\text{mm}$ (0.008inch) unless otherwise noted;
3. Resin color: water clear.


★ Soldering iron

Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter (+10°C → -1sec). Power dissipation of iron should be smaller than 15W, and temperatures should be controllable. Surface temperature of the device should be under 230°C .

★ Recommended Soldering Pattern For Reflow Soldering



★ Recommended Reflow Soldering Profile.



③ Absolute Maximum Ratings:

Series	I _F (mA)	*I _{FP} (mA)	V _R (V)	T _{OP} (°C)	T _{ST} (°C)
GH-2510	30	120	5	-40~+80	-40~+85

★Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width