High Surge Current (D-rated) SIDACtor Device



DO-214AA *SIDACtor* solid state protection devices with a D surge rating protect telecommunications equipment such as modems, line cards, fax machines, and other CPE.

These *SIDACtor* devices withstand simultaneous surges incurred in GR 1089 lightning tests. (See "First Level Lightning Surge Test" on page 4-5.) Surge ratings are twice that of a device with a C surge rating. This allows a discrete surface mount version of Teccor's patented "Y" configuration. (US Patent 4,905,119)

SIDACtor devices are used to enable equipment to meet various regulatory requirements including GR 1089, ITU K.20, K.21 and K.45, IEC 60950, UL 60950, and TIA-968 (formerly known as FCC Part 68).

Electrical Parameters

Part Number *	V _{DRM} Volts	V _S Volts	V _T Volts	Ι _{DRM} μAmps	l _S mAmps	I _T Amps ***	l _H mAmps	C _O pF
P0080SD **	6	25	4	5	800	2.2	50	200
P0300SD **	25	40	4	5	800	2.2	50	220
P0640SD **	58	77	4	5	800	2.2	50	100
P0720SD **	65	88	4	5	800	2.2	50	100
P0900SD **	75	98	4	5	800	2.2	50	100
P1100SD	90	130	4	5	800	2.2	50	80
P1300SD	120	160	4	5	800	2.2	50	80
P1500SD	140	180	4	5	800	2.2	50	80
P1800SD	170	220	4	5	800	2.2	50	60
P2300SD	190	260	4	5	800	2.2	50	60
P2600SD	220	300	4	5	800	2.2	50	60
P3100SD	275	350	4	5	800	2.2	50	60
P3500SD	320	400	4	5	800	2.2	50	60

* For surge ratings, see table below.

** Contact factory for release date.

*** The 2.2 A version cannot be used to meet 4.4 A requirements.

General Notes:

All measurements are made at an ambient temperature of 25 °C. IPP applies to -40 °C through +85 °C temperature range.

· IPP is a repetitive surge rating and is guaranteed for the life of the product.

· Listed SIDACtor devices are bi-directional. All electrical parameters and surge ratings apply to forward and reverse polarities.

V_{DRM} is measured at I_{DRM}.

+ V_{S} is measured at 100 V/µs.

• Special voltage (V_S and V_{DRM}) and holding current (I_H) requirements are available upon request.

• Off-state capacitance (C_O) is measured at 1 MHz with a 2 V bias and is a typical value.

Surge Ratings

Series	l _{PP} 2x10 μs Amps	l _{PP} 8x20 μs Amps	l _{PP} 10x160 μs Amps	l _{PP} 10x560 μs Amps	l _{PP} 10x1000 μs Amps	I _{TSM} 60 Hz Amps	di/dt Amps/µs
D	1000	800	400	300	200	50	1000

Data Sheets

Thermal Considerations

Package	Symbol	Parameter	Value	Unit
DO-214AA	TJ	Operating Junction Temperature Range	-40 to +150	°C
	Ts	Storage Temperature Range	-65 to +150	°C
	$R_{ heta JA}$	Thermal Resistance: Junction to Ambient	90	°C/W



V-I Characteristics



Normalized V_S Change versus Junction Temperature



t_r x t_d Pulse Wave-form



Normalized DC Holding Current versus Case Temperature